

# DOUBLE CAPE COD RAIL GATE

## Double Gate Configuration

(4' & 10' WIDE 46" HIGH GATES)

REAR EYE HINGES (Product Codes #8324)

### GATE HUNG BETWEEN POSTS


Distance between gate and hinge post	A
Width of Left Gate	B
Distance between gates	C
Width of Right Gate	D
Distance between gate and hinge post	E
Total distance between posts	F

Hardware Required								
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rear Eye Hinge Advantages					
Hinge Sets	1 of 8324-S122 & 1 of 8324-S242	1 of 8324-S12P & 1 of 8324-S24P	Opens 180 degrees Incredible amount of adjustment Easy operation & Very Strong Minimal distance between gate and post					
Fasteners included with straps	Two Sets Include: two 12" double strap (8324-122 or 8324-12SP) two 24" double strap (8324-242 or 8324-24SP) four mounting plate with 8" adjustable threaded pins(8256-342 or 8256-34P)							
Mounting Plate Fasteners*	4 of FP-8256-G	4 of FP-8256-B						
Cane Bolt (Vertical)**	1 or 2 of 5000-242	1 or 2 of 5000-24SP	Dimensions (feet and inches)					
	<b>Central Latch Options</b>		A	B	C	D	E	F
Throw Over Gate Loop	4200-032	4200-03SP	1"	4'	1"	10'	1"	14' 3"
Slide Bolt Latch	5002-L122	5002-L12SP	1"	4'	1"	10'	1"	14' 3"
Lumber Required								
Posts	2 of 10' x 6" x 6" (usually dressed out at 5.5" x 5.5")							
	Rails, Stiles (uprights) and Diagonals made from full 1" thick by 5.5" wide lumber (commonly stocked decking material or rough cut lumber)							
Rails	2 of 8' x 1" x 5.5" and 4 of 10' x 1" x 5.5"							
Stiles	6 of 8' x 1" x 5.5"							
Diagonals	2 of 8' x 1" x 5.5" and 2 of 12' x 1" x 5.5"							
Filler blocks for bottom hinge	1 of 12' x 1" x 5.5" and 2 of 14' x 1" x 5.5" (Parts E,F,G and H on Plan Layout)							
Fasteners Required for Gate Construction								
	2 of FP-CapeCod- Fastener Pack for Cape Cod Gate Build (Each pack includes 50 of 1.75" wood screws, 18 of 3.5" HDG carriage bolts nuts and washers)							
	*Mounting Plate Fasteners - 20 of 3/8" carriage bolts for posts up to 5.5" thick <b>OR</b> Purchase separately 20 of 3/8" lag bolts (minimum of 4" long)							
	**One 24" Cane Bolt (5000-242 or 5000-24SP) is required for central stability. Two are needed if you require a means of keeping the gates open.							


#### SNUG COTTAGE HARDWARE

Download includes this materials list, component cutting and layout sheet, tips on installing gate posts, and detailed instructions.




For a complete listing of our free gate plans and gate layouts visit [snugcottagehardware.com](http://snugcottagehardware.com).






**FLAT FRONTAL VIEW**




**THREE LAYERS**




**COMPONENTS (FULL 1" THICK x 5-1/2" WIDE)**






**Snug Cottage Hardware**  
4' Cape Cod Board Gate








**FLAT FRONTAL VIEW**



**THREE LAYERS**



**COMPONENTS (FULL 1" THICK x 5-1/2" WIDE)**



**Snug Cottage Hardware**  
10' Cape Cod Board Gate

For Rear Eye  
Hinge Only