


DOUBLE MAINE BOARD RAIL GATE

Double Gate Configuration

(4' & 5' WIDE 46" HIGH GATES)

REAR EYE HINGES (Product Codes #8324)

GATE HUNG BETWEEN POSTS




Distance between gate and hinge post	A
Width of Left Gate	B
Distance between gates	C
Width of Right Gate	D
Distance between gate and hinge post	E
Total distance between posts	F

Hardware Required										
	Galvanized Finish		Black Powder Coat over Galvanized Finish		Rear Eye Hinge Advantages Opens 180 degrees Incredible amount of adjustment Easy operation & Very Strong Minimal distance between gate and post					
Hinge Sets	1 of 8324-S122 & 1 of 8324-S182		1 of 8324-S12P & 1 of 8324-S18P							
Fasteners are included with straps	Two Sets Include: 2 of 12" double strap (8324-122 or 8324-12SP) & 2 of 18" double strap (8324-182 or 8324-18SP) 4 of mounting plate with 8" adjustable threaded pins(8256-342 or 8256-34P)									
Mounting Plate Fasteners*	FP-8256-G x4		FP-8256-B x4							
Cane Bolt (Vertical)**	1 or 2 of 5000-242		1 or 2 of 5000-24SP							
	Central Latch Options				Dimensions (feet and inches)					
					A	B	C	D	E	F
Throw Over Gate Loop	4200-032		4200-03SP		1"	4'	1"	6'	1"	10' 3"
Slide Bolt Latch	5002-L122		5002-L12SP		1"	4'	1"	6'	1"	10' 3"
Lumber Required										
Posts	2 of 8' x 6" x6" (usually dressed out at 5.5" x 5.5")									
Rails, Stiles (uprights) and Diagonals made from full 1" thick by 5.5" wide lumber (commonly stocked decking material or rough cut lumber)										
Rails	3 of 8' x 1" x 5.5" and 3 of 12' x 1" x 5.5"									
Stiles	4 of 8' x 1" x 5.5"									
Diagonals	1 of 10' x 1" x 5.5" and 1 of 14' x 1" x 5.5"									
Filler blocks for bottom hinge	1 of 8' x 1" x 5.5"									
Fasteners Required for Gate Construction										
2 of FP-Maine- Fastener Pack for Maine Board Gate Build (Each pack includes 40 of 1.75" wood screws, 14 of 3.5" HDG carriage bolts nuts and washers)										
*Mounting Plate Fasteners -20 of 3/8" carriage bolts for posts up to 5.5" thick OR Purchase separately 20 of 3/8" lag bolts (minimum of 4" long)										
**One 24" Cane Bolt (5000-242 or 5000-24SP) is required for central stability. Two are needed if you require a means of keeping the gates open.										


SNUG COTTAGE HARDWARE

Download includes this materials list, component cutting and layout sheet, tips on installing gate posts, and detailed instructions.




For a complete listing of our free gate plans and gate layouts visit snugcottagehardware.com.








FLAT FRONTAL VIEW




THREE LAYERS




COMPONENTS (FULL 1" THICK x 5-1/2" WIDE)






Snug Cottage Hardware
4' Maine Board Gate








FLAT FRONTAL VIEW



THREE LAYERS



COMPONENTS (FULL 1" THICK x 5-1/2" WIDE)



Snug Cottage Hardware
5' Maine Board Gate