

SINGLE MAINE BOARD RAIL GATE

Single Gate Configuration

(4 FOOT WIDE 46" HIGH GATES)

CENTRAL EYE HINGES (Product Codes #8312)

GATE HUNG BETWEEN POSTS

Distance between latch post and gate	Α
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required					
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Centre	Central Eye Hinge Advantages			
Hinge Set	8312-\$122	8312-S12P					
		Set Includes	Open	Opens both ways 100 degrees			
All fasteners are included	one 12 inch double strap (8312-422 or 8312-42SP)			Incredible amount of adjustment			
with hardware	one adjustable bottom gate fitting (8250-002 or 8250-00P)		Easy operation				
	two 12" adjustable gate pin (8801-122 or 8801-12P)		Very strong				
	Central Latch Options		Dimensions (feet and inches)				
			Α	В	С	D	
Irish Gate Latch (shown above)	8328-002	8328-00SP	1''	4'	4.5"	4' 5.5"	
Quick Catch	4100-3\$\$	4100-3BSS	1.5"	4'	4.5"	4'-6"	
Spring Latch	8327-002	8327-00P	4''	4'	4.5"	4' 9.5"	
Slide Bolt Latch	5002-L122	5002-L12SP	1"	4'	4.5"	4' 5.5"	
	0	ptional Gate Hold Back	•				
Heavy Duty Cabin Hook	4270-122	4270-12SP	A means of keeping gate ope			gate open	
	•	Lumber Required					
Posts	2 of 8' x 6" x6" (usually dressed c	out at 5.5" x 5.5")					
Rails, Stiles (uprights) and	Diagonals made from full 1" thick	by 5.5" wide lumber (commonly stocked decking m	aterial or	rough (cut lumb	er)	
Rails	3 of 8' x 1" x 5.5"						
Stiles	2 of 8' x 1" x 5.5"						
Diagonals	1 of 10' x 1" x 5.5"						
		Required for Gate Construction					
FP-Maine- Fastener Pack for Mair	ne Board Gate Build (Includes 40 d	of 1.75" wood screws, 14 of 3.5" HDG carriage bolts r	iuts and v	vashers)		
	SNI	IG COTTAGE HARDWARE					

